## US005079103A

# United States Patent [19]

# Schramm

[11] Patent Number:

5,079,103

[45] Date of Patent:

Jan. 7, 1992

[54]	FUEL CELLS WITH HYDROGEN RECYCLE		
[75]	Inventor:	Walter Schramm, Munich, Fed. Rep. of Germany	
[73]	Assignee:	Linde Aktiengesellschaft, Wiesbaden, Fed. Rep. of Germany	
[21]	Appl. No.:	514,459	
[22]	Filed:	Apr. 25, 1990	
[30]	Foreign Application Priority Data		
Apr	. 25, 1989 [D	E] Fed. Rep. of Germany 3913581	
[51]	Int. Cl.5	H07M 8/06	
[52]	U.S. Cl		
[58]	Field of Sea	ırch 429/17, 19	
[56]		References Cited	
	TICI	A TENT DOOLINGS	

# U.S. PATENT DOCUMENTS

2,901,524	8/1959	Gorin et al	<b>42</b> 9/17
2,926,753	3/1960	Kohl et al	183/115
3,462,308	8/1969	Winters	<b>42</b> 9/17
4,037,024	7/1977	Landau	429/17
4,042,755	8/1977	Anbar	429/17 X

# FOREIGN PATENT DOCUMENTS

3810113	10/1989	Fed. Rep. of Germany .
60-158559	8/1985	Japan 429/17

### OTHER PUBLICATIONS

Riquarts et al., "Linde Reports on Science and Technology: Gas Separation Using Pressure Swing Adsorption Plants", No. 40, 1985, pp. 26-35.

Linde, "Plants for the Production of Pure Hydrogen from Light Hydrocarbons", 1983.

Voss, "Status of Fuel Cell Development", Fuel Cell Workshop at Taormina/Sicily, Jun. 6, 1987, Comm. of the European Communities.

Primary Examiner—Stephen J. Kalafut Attorney, Agent, or Firm—Millen, White & Zelano

#### [57] ABSTRACT

In high-temperature fuel cells, for example the solid oxide fuel cell (SOFC) and molten carbonate fuel cell (MCFC), anode waste gases containing hydrogen and carbon dioxide are separated from the waste gas stream by means of, e.g., a scrubbing step and/or an adsorption system, and the thus-obtained hydrogen is recycled to the anode. For the operation of an MCFC system, the carbon dioxide separated from the anode waste gas is reused by being admixed to the oxygen stream entering the cathode.

# 9 Claims, 1 Drawing Sheet

